



**TIMBERWOLF®**  
**LEAD THE PACK**

With the largest infeed of its class, and our WolfTrack Fixed Track Dual Speed tracking system, means that operator comfort and safety is engineered in harmony with power and efficiency.

A low-speed gear to negotiate difficult terrain and a higher-speed to cover distance efficiently.



# TW 280FTR

## THE HUNGRY WOLF

With amazing off-road capability, the TW 280FTR is our 'hungry wolf' tracked wood chipper kitted with a powerful Kubota WG1605 57 hp petrol engine.



[www.timberwolf-uk.com](http://www.timberwolf-uk.com)



# TIMBERWOLF®

## LEAD THE PACK

### FEATURES AND BENEFITS:

- Processing throughput of up to 7 tonnes/hr
- 57 hp Kubota petrol engine
- Class-leading 280 mm x 210 mm infeed opening (8 ¼" cutting performance)
- Quad force rollers for ultimate grip, crushing & infeed power
- 245 mm ground clearance
- Anti-vibration folding operator control platform
- WolfTrack Dual Speed Tracking System (Low speed: 2.5 kph High speed: 5 kph)
- Optional Bushy Hall Delta S3300 electric winch
- Integrated track recovery system
- Dual, ergonomic heavy duty infeed controls
- 280° adjustable discharge chute
- Patented exhaust cooler reduces exhaust temperatures up to 300°C
- WolfPort blade access and removeable side panels for easy maintenance and servicing accessibility
- Double-sided reversible blades
- Timberwolf reliability and simplicity built-in
- 3-year warranty as standard with optional 5-year extended warranty

| <b>TW 280FTR SPECIFICATIONS</b>    |  |
|------------------------------------|--|
| <b>PETROL ENGINE</b>               |  |
| 57 hp Kubota (E10 compliant)       |  |
| Fuel tank capacity                 | 36 litres                                    |
| <b>DIMENSIONS</b>                  |  |
| Weight                             | 1592 kg                                      |
| Height                             | 2320 mm                                      |
| Height with discharge tube removed | 1460 mm                                      |
| Length (tray down)                 | 3665 mm                                      |
| Length (tray up)                   | 2880 mm                                      |
| Width                              | 1410 mm                                      |
| <b>CHIPPING FEATURES</b>           |  |
| Feed method                        | Twin hydraulic rollers c/w Auto Feed Control |
| Maximum diameter infeed            | 210 mm (8 ¼")                                |
| Discharge tube                     | 280° adjustable discharge                    |
| Blades                             | 2 x 158 mm double sided, fully hardened      |